

# Magellan® 2200VS Ω

Vertical Scanner



## Mechanical

### Dimensions

Height: 6.0" / 15.2 cm

Width: 6.0" / 15.2 cm

Depth: 3.83" / 9.7 cm

Weight: 2.5 lb / 1.1 kg

## Environmental

### Temperature rating

Operating: 50° to 104° F / 10° to 40° C

Storage/transport: -40° to 158° F / -40° to 70° C

### Humidity

Operating: 5 to 95% NC

Storage/transport: 5 to 95% NC

## Optical

Scan lines: 20

Motor Speed: 6,000 RPM

Depth-of-field: 8.0" / 23.3 cm

Read height: 6.0" / 15.2 cm

## Decoding Capability

The Magellan® 2200VS Ω autodiscriminates between all of the following supported symbologies:

- UPC Versions A&E
- UPC Supplementals (Bookland & Coupon Code)
- UPC Add-ons (sub 2 or P2, sub 5 or P5 & CI28)
- Reduced Space Symbology (RSS-14, expanded and stacked)
- EAN 8, 13
- JAN 8, 13
- EAN/JAN two label
- UCC/EAN 128
- Code 39 (with full ASCII)
- Code 128
- Code 93
- Interleaved 2 of 5
- Standard 2 of 5
- Italian Pharmacode
- Codabar/NW7
- MSI/Plessey

## Features:

- Omega Tek™ Productivity Technology
- Aggressive vertical scan volume
- FirstStrike® advanced decoding software
- RSS Decoding capability
- Flash memory for easy software upgrades
- Multiple interface solution supports all popular host interfaces
- Powered auxiliary RS-232 port for easy integration of a handheld scanner
- Host diagnostic reporting
- Optional EAS functionality
- Optional Productivity Index Reporting™ Software
- 2005 Sunrise compliant



"Nothing Beats a Magellan®"



Copyright © PSC Inc. 2005. All rights reserved. Protected to the fullest extent under U.S. and international laws. Copying, or altering of this document is prohibited without express written consent from PSC. PSC Inc. of Eugene, Oregon, USA is ISO registered by NQA. PSC, the PSC logo, Magellan, and First Strike are registered trademarks of PSC Inc. Productivity Index Reporting (PIR) is a trademark of PSC Inc. All other brand and product names are trademarks of their respective owners. Additional information concerning this product or other PSC products and services can be found at the PSC web site: [www.psc.com](http://www.psc.com). Product specifications are subject to change without notice.



R40-004-US 1 1005

# Data Sheet

## Electrical

### AC Power requirements

90-265 VAC, 47-63 Hz

4.0 Watts (nominal)

9.6 Watts (maximum)

2.5 Watts (sleep mode)

## Communications

Host: Standard RS-232, IBM 46XX, IBM USB, USB Keyboard, Keyboard Wedge

Other: Powered RS-232 auxiliary port

## Safety and Regulatory

Electrical: EN60 950 (TUV Europe) PSE-Mark (Japan); UL60950 (USA) CSA 60950 (Canada)

Emissions: CISPR22-B (World), FCC part 15 Class B (USA), VCCI-B (Japan), EN 55022-B (Europe), NOM (Mexico)

Laser Safety: CDRH Class IIa (USA/Canada), EN 60825-1 Class 1 (Europe), IEC 60825-1 Class 1 (World)



(CAUTION: Laser Radiation – do not stare into beam);

IEC 60825 Class 1 (Europe)



## Other

EAS compatibility: Integrated EAS hardware will work with Counterpoint IV, V, VI and VII models available from Checkpoint® Systems.

Good read acknowledgement with Sensomatic. OPOS and JPOS compatible.

PSC Inc.

959 Terry Street

Eugene OR 97402-9150 USA

Tel: 800 695 5700 or 541 683 5700

Fax: 541 345 7140

